



I.G.B.T. 變頻式直流氬銲機(手提型)

項目 Item	機型 model	T-200	T-302A
控制系統 Control System		I.G.B.T. 變頻式	
入力電壓 Input Voltage		1 ϕ 220V 50/60HZ	1 ϕ 3 ϕ 220V 50/60HZ
定格入力 Rated Input		5KVA	12KVA
空載電壓 Open Circuit Voltage		65V	70V
初期電流 Start Current		4~200A	4~300A
熔接電流 Welding Current		4~200A	4~300A
收弧電流 Crater Filler Current		4~200A	4~300A
定格使用率 Duty Cycle		40%	40%
被覆銲 Stick Welding		4~185A	4~250A
外型尺寸 Dimensions		L350xW215xH330(mm)	L420xW240xH380(mm)
重量 Weight		14KG	22KG



I.G.B.T. 變頻式直流/交直流脈波氬銲機(重負荷型)

項目 Item	機型 model	T-300	T-400	T-500	T310ADP	T410ADP	T510ADP
控制系統 Control System		I.G.B.T. 變頻式					
入力電壓 Input Voltage		1 ϕ 3 ϕ 220V 50/60HZ					
定格入力 Rated Input		12KVA	16KVA	18KVA	12KVA	16KVA	18KVA
空載電壓 Open Circuit Voltage		70V	70V	70V	70V	70V	70V
初期電流 Start Current		5~300A	5~400A	5~500A	5~300A	5~400A	5~500A
熔接電流 Welding Current		5~300A	5~400A	5~500A	5~300A	5~400A	5~500A
收弧電流 Crater Filler Current		5~300A	5~400A	5~500A	5~300A	5~400A	5~500A
脈波電流 Pulse Current		—	—	—	5~300A	5~400A	5~500A
脈波頻率 Pulse Freq		—	—	—	Low 0.5~25Hz Mid 10~500Hz	Low 0.5~25Hz Mid 10~500Hz	Low 0.5~25Hz Mid 10~500Hz
定格使用率 Duty Cycle		60%	60%	60%	60%	60%	60%
被覆銲 Stick Welding		5~240A	5~350A	5~450A	5~240A	5~350A	5~450A
外型尺寸 Dimensions		L440xW330xH550 (mm)	L540xW410xH720 (mm)	L540xW410xH710 (mm)	L440xW330xH635 (mm)	L560xW410xH720 (mm)	L560xW410xH720 (mm)
重量 Weight		32KG	60KG	70KG	55KG	60KG	70KG